

## ADC53



- Recommend to use
- Permitted
- Not recommended to use

- » Drive wheel suitable for mixed road surface and poor road condition.
- » Double nylon reinforce for bead improves load capacity.
- » Excellent bead endurance performance to overcome overload and under-inflation.
- » The application of high intensity HT cord increases 30% carcass strength comparing with the normal cord.
- » Optimized design of the tyre tread ensures even wear. Good performance of grip, traction and drainage.



Size	Ply Rating	Single Max. Load(kg)	DualMax. Load(kg)	Single Max Pressure(kPa)	Dual Max Pressure(kPa)	LI/SS	Second. LI/SS	Tread depth	ECE	Inmetro	M+S
								(mm)			
10.00R20	18	3250	3000	930	930	149/146K		17.5	√		√
11.00R20	18	3550	3250	930	930	152/149K		18.5	√	I	√
11R22.5	16	3000	2725	830	830	146/143L	148/145K	22.5	√	I	√
11R24.5	16	3250	3000	830	830	149/146L		22.5			√
12.00R20	18	3750	3450	830	830	154/151K		20.6	√	I	√
12.00R20	22	4250	3875	970	970	158/155J		20.6	√		√
12.00R24	20	4500	4125	900	900	160/157K		20.6	√	I	√
12R22.5	18	3550	3250	930	930	152/149L		19.5	√	I	√
13R22.5	18	3750	3450	830	830	154/151K	156/150G	20.6	√	I	√
275/70R22.5	18	3150	2900	900	900	148/145L		17.5	√		√
295/80R22.5	18	3550	3250	900	900	152/149L		19	√	I	√
315/80R22.5	18	3750	3450	830	830	154/151M	156/150L	19.5	√	I	√
315/80R22.5	20	4125	3750	900	900	157/154M		19.5	√	I	√