

# MT

# TRAVIA M/T

## Long Mileage Solution

- High abrasion tread compound to enhance expected mileage markedly.

## Low Failure Solution

- Specially designed shoulder curve can effectively protect against overwear and avoid early damage.

## High Load Solution

- Reinforced tyre body and band structure to provide stronger load capacity.



NO.	Series	Size	SL/XL	Sidewall Type	Rim	PR	LI/SS	Max. Load Capacity (KG)	Max. Load Capacity (LBS)	Max. Air Pressure (KPa)	Max. Air Pressure (PSI)	Tread Depth (mm)	Section Width (mm)	Overall Diameter (mm)
1	50"	33X12.50R18LT	-	OWL	10.0	10	118Q	1320	2910	450	65	15	318	826
2		33X12.50R20LT	-	OWL	10.0	10	114Q	1180	2600	450	65	15	318	826
3	60"	35X12.50R20LT	-	OWL	10.0	10	121Q	1450	3195	450	65	15	318	877
4	70"	LT265/70R17	-	OWL	8.0	10	121/118Q	1450/1320	3195/2910	550	80	15	272	804
5		LT285/70R17	-	OWL	8.5	10	121/118Q	1450/1320	3195/2910	550	80	15	292	832
6	75"	31X10.50R15LT	-	OWL	8.5	6	109Q	1030	2270	350	50	15	268	775
7		LT245/75R16	-	OWL	7.0	10	120/116Q	1400/1250	3085/2755	550	80	15	248	774
8		LT265/75R16	-	OWL	7.5	10	123/120Q	1550/1400	3415/3085	550	80	15	267	804
9		LT285/75R16	-	OWL	8.0	10	126/123Q	1700/1550	3750/3415	550	80	15	286	834