



FR:01™ II

THE MOST VERSATILE TYRE IN PIRELLI BRANDED RANGE, FOR USE IN HIGHWAY AND REGIONAL APPLICATIONS IN ALL WEATHER CONDITIONS PERFORMING AT HIGH LEVEL IN SNOW GRIP AND WET BRAKING, DRY AND WET HANDLING, EVEN WEAR.



TREAD DESIGN

- **Increased tread width** to favour:
 - higher mileage
 - road holding and steering precision
- **Ejectors** at the bottom of central grooves prevent stones trapping.
- **Four zig-zag grooves** and robust **longitudinal ribs** are designed to reduce braking distance and enhance driving safety.
- **Innovative shoulder tread contour** (Pirelli patent) that allows optimum distribution of footprint contact pressure, favouring even wear and therefore increasing mileage.

TREAD COMPOUND

- Innovative compound, to drive further in safety.
- The **new tread compound** formula and the **high content of silica** ensure high mileage and resistance to the stress typical of tyres intended for mixed use, even on moderately abrasive surfaces.
- **Performance in dry, wet and winter conditions** is improved whilst maintaining high safety levels for the entire life of the tyre.

SIZE	LOAD INDEX/SPEED CODE	MARKINGS	EFFICIENCY LABELS		
9.00R20 TT	140/137 L		designed for APAC		
10.00R20 TT	146/143 K		designed for APAC		
8R22.5 TL	130/128 M	M+S	designed for APAC		
9R22.5 TL	136/134 M	M+S	designed for APAC		
10R22.5 TL	144/142 M	M+S	designed for APAC		
11R22.5 TL	148/145 L	M+S	designed for APAC		
12R22.5 TL	145/148 M	M+S	designed for APAC		
255/70R22.5 TL	140/137 M	M+S	designed for APAC		
275/70R22.5 TL	148/145 M	M+S	designed for APAC		
295/80 R 22.5	152/148 M	3PMSF M+S	C	B	71 dB
295/80 R 22.5	154/149 M XL	3PMSF M+S XL	C	B	71 dB
315/70R22.5 TL	156/150L (154/150M) XL	3PMSF M+S XL	C	B	72 dB
315/80R22.5 TL	156/150L (154/150M)	3PMSF M+S	C	A	70 dB