



## ST:O1™ 17.5" / 19.5"

DESIGNED FOR FITMENT OF TRAILER AND SEMI-TRAILER TO ENSURE RESISTANCE TO LOAD, ROBUSTNESS, MILEAGE AND RETREADABILITY.





- Increased tread width and groove depth to enhance mileage
- Reinforced sidewalls provide resistance to lateral impacts and abrasion
- 4 Zig-zag shape grooves and robust ribs designed to deliver great lateral holding as well as high tear resistance
- Optimized tread profile for a correct distribution of footprint contact pressure, able to improve even wear and ensure high mileage





|               |                       |          | EFFICIENCY LABELS |   |               |
|---------------|-----------------------|----------|-------------------|---|---------------|
| SIZE          | LOAD INDEX/SPEED CODE | MARKINGS | <b>(6.</b> P)     |   | <b>(C</b> -4) |
| 205/65 R 17.5 | 129/127 J             | M+S FRT  | D                 | В | 70 dB         |
| 215/75 R 17.5 | 135/133 J             | M+S FRT  | D                 | В | 70 dB         |
| 235/75 R 17.5 | 143/141 J             | M+S FRT  | С                 | С | 69 dB         |
| 245/70 R 17.5 | 143/141 J             | M+S FRT  | С                 | С | 69 dB         |
| 245/70 R 19.5 | 141/140 J             | M+S FRT  | D                 | С | 71 dB         |
| 265/70 R 19.5 | 143/141 J             | M+S FRT  | D                 | Α | 72 dB         |
| 285/70 R 19.5 | 150/148 J             | M+S FRT  | D                 | Α | 72 dB         |