

AP866 *ON OFF ROAD* *ALL-POSITION*

Size	Standard Rim	PR	Load				Pressure				Load Index		TreadDepth (mm)	Speed Grade	Inflated Tire Dimension (mm)	
			KG		lbs		kPa		psi		S	D			D	B
			S	D	S	D	S	D	S	D	S	D				
CN 6.50R16LT	5.50F,5 1/2J	12	1060	925	2335	2040	670	670	97	97	110	105	10.5	K	750	185
CN/VN 7.00R16LT	5.50F	14	1320	1180	2910	2600	770	770	112	112	118	114	12.5	L	775	200
CN/VN 7.50R16LT	6.00G	14	1500	1320	3305	2910	770	770	112	112	122	118	12.5	L	805	215
CN/VN 8.25R16LT	6.50H	16	1800	1600	3970	3525	770	770	112	112	128	124	13.5	L	865	235
CN/VN 8.25R20	6.5	16	2430	2300	5355	5070	930	930	135	135	139	137	13	K	974	236
CN/VN 9.00R20	7.0	16	2800	2650	6170	5840	900	900	130	130	144	142	15	K	1019	259
CN/VN 10.00R20	7.5	18	3250	3000	7160	6610	930	930	135	135	149	146	16	K	1054	278
CN 11.00R20	8.0	18	3550	3250	7830	7160	930	930	135	135	152	149	16.5	K	1085	293
CN 12.00R20	8.5	18	3750	3450	8270	7610	830	830	120	120	154	151	17	K	1125	315
CN/VN 11R22.5	8.25	16	3150	2900	6940	6395	850	850	123	123	148	145	16	M	1065	279
CN 12R22.5	9.00	18	3550	3250	7830	7160	930	930	135	135	152	149	16.5	K	1085	300
VN 13R22.5	9.75	18	3750	3350	8270	7390	850	850	125	125	154	150	16	L	1124	320
VN 315/80R22.5	9.00	20	4000	3650	8820	8045	850	850	125	125	156	153	16	K	1076	312
CN/VN 11R24.5	8.25	16	3250	3000	7160	6610	830	830	120	120	149	146	16	M	1104	279
CN 315/80R22.5	9.00	20	4000	3650	8820	8045	850	850	125	125	156	153	16.0	K	1076	312
CN 13R22.5	9.75	18	3750	3350	8270	7390	850	850	125	125	154	150	16.0	L	1124	320
CN 12.00R24	8.5	20	4500	4125	9930	9090	900	900	130	130	160	157	14.0	K	1210	308
CN 295/80R22.5	9.00	16	3550	3150	7830	6940	850	850	123	123	152	148	17.5	M	1044	298
CN 295/80R22.5	9.00	18	3550	3250	7830	7160	900	900	130	130	152	149	17.5	L	1044	298

The RoadX AP866 is an all-position rib suitable for both on and off-road applications. The AP866 was engineered with extended tread life in mind, and designed to deliver class-leading chip resistance.

TIRE FEATURES:

- 1 The large, deep shoulder grooves increase traction.
- 2 The unique tread groove angle and inner groove design significantly improves grip and traction, while also providing great directional stability. This promotes even tire wear and makes it adaptable to various road surfaces.
- 3 Widened running surface pattern with compounding that provides excellent puncture and abrasion resistance.

