

HN08



- Recommend to use
- Permitted
- Not recommended to use

- » Steer, drive and trailer wheel
- » Suitable for relatively poor road condition;
- » Great anti-uneven wear ability and high tear resistance
- » Low heat generating and great rear resistance character.



Size	Ply Rating	Single Max. Load(kg)	DualMax. Load(kg)	Single Max Pressure(kPa)	Dual Max Pressure(kPa)	LI/SS	Second. LI/SS	Tread depth	ECE	Inmetro	M+S
								(mm)			
11/2R24	18	4250	3875	830	830	158/155K		17.5			√
10R22.5	16	2800	2650	900	900	144/142L		15.5	√	I	√
10.00R20	16	3000	2725	830	830	146/143K		16.5	√	I	√
10.00R20	18	3250	3000	930	930	149/146K		16.5	√	I	√
11.00R20	18	3550	3250	930	930	152/149K		17	√		√
11R22.5	16	3000	2725	830	830	146/143L	148/145K	17	√	I	√
11R24.5	16	3250	3000	830	830	149/146L		16.5		I	
12.00R20	18	3750	3450	830	830	154/151K		17.5	√	I	√
12.00R20	20	4000	3650	900	900	156/153K		17.5			√
12.00R24	18	4250	3875	830	830	158/155K		17.5	√	I	√
12.00R24	20	4500	4125	900	900	160/157K		17.5	√	I	√
12R22.5	18	3550	3250	930	930	152/149L		17	√	I	√
315/80R22.5	18	3750	3450	830	830	154/151L	156/150K	16.5	√	I	√
315/80R22.5	20	4625	3750	900	900	161/154K		16.5		I	√
315/80R22.5	22	4535	4125	900	900	160/157L		16.5			√
7.00R16	14	1320	1180	770	770	118/114L		13	√		
7.50R16	14	1500	1320	770	770	122/118L		13	√	I	√
8.25R16	14	1700	1500	670	670	126/122L		13	√		√
8.25R16	16	1800	1600	770	770	128/124L		13	√		√
8.25R20	14	2240	2120	830	830	136/134K		14.5	√	I	√
8.25R20	16	2430	2300	930	930	139/137K		14.5			√
9.00R20	16	2800	2650	900	900	144/142K		15.5	√	I	√