

## Low Failure Solution

- High turn-up belt structure to avoid early damage.

## Transport Efficiency Solution

- Silicious compound to enhance low rolling resistance.

## Noise Reduction Solution

- Optimized pattern pitch to reduce rolling noise.

## All-weather Grip Solution

- Special compound combined with zigzag steel disc to enhance outstanding wet grip.

## Travel Comfort Solution

- Enable special production line of the most advanced equipment to ensure ride comfort.



NO.	Series	Size	SL/XL	Sidewall Type	Rim	PR	LI/SS	Max. Load Capacity (KG)	Max. Load Capacity (LBS)	Max. Air Pressure (KPa)	Max. Air Pressure (PSI)	Tread Depth (mm)	Section Width (mm)	Overall Diameter (mm)
1	40"	165/40R16	XL	BSW	6.0	-	73V	365	805	340	50	7.2	170	538
2	45"	165/45R16	XL	BSW	5.5	-	74V	375	827	340	50	7.2	165	554
3	50"	165/50R15	SL	BSW	5.0	-	72V	355	783	350	51	7.4	170	547
4	55"	155/55R14	SL	BSW	5.0	-	69H	325	716	350	51	7.2	162	526
5		165/55R14	SL	BSW	5.0	-	72H	355	783	350	51	7.4	170	538
6		165/55R15	SL	BSW	5.0	-	75V	387	853	350	51	7.2	170	563
7		185/55R15	SL	BSW	6.0	-	82H	475	1047	350	51	7.4	194	585
8		185/55R15	SL	BSW	6.0	-	82V	475	1047	350	51	7.4	194	585
9	60"	165/60R14	SL	BSW	5.0	-	75H	387	853	350	51	7.4	170	554
10		185/60R14	SL	BSW	5.5	-	82H	475	1047	350	51	7.4	189	578
11		185/60R15	SL	BSW	5.5	-	84H	500	1102	350	51	7.4	189	603
12		185/60R15	XL	BSW	5.5	-	88H	560	1235	340	50	7.4	189	603
13	65"	175/65R14	SL	BSW	5.0	-	82T	475	1047	350	51	7.4	177	584
14		175/65R14	SL	BSW	5.0	-	82H	475	1047	350	51	7.4	177	584
15		175/65R14	XL	BSW	5.0	-	86T	530	1168	340	50	7.4	177	584
16		175/65R15	SL	BSW	5.0	-	84H	500	1102	350	51	7.4	177	609
17		185/65R14	SL	BSW	5.5	-	86H	530	1168	350	51	7.4	189	596
18		185/65R15	SL	BSW	5.5	-	88H	560	1235	350	51	7.4	189	621
19		185/65R15	SL	BSW	5.5	-	88T	560	1235	350	51	7.4	189	621
20		185/65R15	XL	BSW	5.5	-	92T	630	1389	340	50	7.4	189	621
21	70"	145/70R12	SL	BSW	4.5	-	69T	325	716	350	51	7.2	150	509
22		145/70R13	SL	BSW	4.5	-	71T	345	761	350	51	7.2	150	534
23		155/70R13	SL	BSW	4.5	-	75T	387	853	350	51	7.4	157	548
24		165/70R13	SL	BSW	5.0	-	79T	437	963	350	51	7.4	170	562
25		165/70R13	XL	BSW	5.0	-	83T	487	1074	340	50	7.4	170	562
26		165/70R14	SL	BSW	5.0	-	81T	462	1019	350	51	7.4	170	588
27		165/70R14	XL	BSW	5.0	-	85T	515	1135	340	50	7.4	170	588
28		175/70R13	SL	BSW	5.0	-	82T	475	1047	350	51	7.4	177	576
29		175/70R14	SL	BSW	5.0	-	84T	500	1102	350	51	7.4	177	602
30		175/70R14	XL	BSW	5.0	-	88T	560	1235	351	50	7.4	177	602
31		185/70R13	SL	BSW	5.5	-	86T	530	1168	350	51	7.4	189	590
32		185/70R14	SL	BSW	5.5	-	88T	560	1235	350	51	7.4	189	616
33	75"	175/75R13	SL	BSW	5.0	-	84T	500	1102	350	51	5.7	177	593
34		175/75R14	SL	BSW	5.0	-	86T	530	1168	350	51	5.7	177	618
35	80"	155/80R13	SL	BSW	4.5	-	79T	437	963	350	51	7.4	157	578