

# AT

# TRAVIA A/T

## Long Mileage Solution

- High abrasion tread compound combined with widened tread width to enhance expected mileage markedly.

## Low Failure Solution

- Specially designed shoulder curve can effectively protect against overwear and avoid early damage.



## All-weather Grip Solution

- Multiple Wide grooves to provide excellent drainage performance and wet grip.

## High Load Solution

- Reinforced tyre body and band structure to provide stronger load capacity.

NO.	Series	Size	SL/XL	Sidewall Type	Rim	PR	LI/SS	Max. Load Capacity (KG)	Max. Load Capacity (LBS)	Max. Air Pressure (KPa)	Max. Air Pressure (PSI)	Tread Depth (mm)	Section Width (mm)	Overall Diameter (mm)
1	60"	205/60R16	SL	OWL	6.0	-	92H	630	1389	350	51	8.2	209	652
2		205/65R15	SL	OWL	6.0	-	94H	670	1477	350	51	8.2	209	647
3	65"	235/65R17	SL	OWL	7.0	-	104T	900	1984	350	51	10.5	240	738
4		245/65R17	SL	OWL	7.0	-	107T	975	2149	350	51	10.5	248	750
5		265/65R17	SL	OWL	8.0	-	112H	1120	2469	350	51	10.5	272	776
6		205/70R15	SL	OWL	6.0	-	96T	710	1565	350	51	8.2	209	669
7		215/70R16	SL	OWL	6.5	-	100H	800	1764	350	51	10.5	221	708
8		225/70R16	SL	OWL	6.5	-	103T	875	1929	350	51	10.5	228	722
9		235/70R16	SL	OWL	7.0	-	106T	950	2094	350	51	10.5	240	736
10	70"	245/70R16	XL	BSW	7.0	-	111T	1090	2403	340	50	10.5	248	750
11		245/70R16	SL	OWL	7.0	-	107T	975	2149	350	51	10.5	248	750
12		265/70R16	SL	OWL	8.0	-	112T	1120	2469	350	51	10.5	272	778
13		265/70R17	SL	OWL	8.0	-	115T	1215	2679	350	51	10.5	272	804
14		LT265/70R17	-	OWL	8.0	10	121/118R	1450/1320	3195/2910	550	80	12.5	272	804
15		LT285/70R17	-	OWL	8.5	8	121/118S	1450/1320	3195/2910	450	65	12.5	292	832
16		205/75R15	SL	OWL	6.0	-	96T	710	1565	350	51	8.2	209	669
17		215/75R15	SL	OWL	6.0	-	100T	800	1764	350	51	10.5	216	703
18		235/75R15	XL	OWL	6.5	-	109T	1030	2271	340	50	10.5	235	733
19		265/75R16	SL	OWL	7.5	-	116T	1250	2756	350	51	10.5	267	804
20		31X10.50R15LT	-	OWL	8.5	6	109R	1030	2270	350	50	12.5	268	775
21	75"	LT225/75R16	-	OWL	6.0	10	115/112R	1215/1120	2680/2470	550	80	12.5	223	744
22		LT235/75R15	-	OWL	6.5	10	116/113S	1250/1150	2755/2535	550	80	12.5	235	733
23		LT245/75R16	-	OWL	7.0	10	120/116R	1400/1250	3085/2755	550	80	12.5	248	774
24		LT245/75R17	-	OWL	7.0	10	121/118R	1450/1320	3195/2910	550	80	12.5	248	800
25		LT265/75R16	-	OWL	7.5	10	123/120R	1550/1400	3415/3085	550	80	12.5	267	804