

Long Mileage Solution

- High abrasion tread compound combined with widened tread width to enhance expected mileage markedly.

Transport Efficiency Solution

- Professional shoulder block to enhance excellent riding stability at high speed.



Noise Reduction Solution

- Wide groove compound combined with corrugated steel disc to enhance expected mileage markedly.

NO.	Series	Size	SL/XL	Sidewall Type	Rim	PR	LI/SS	Max. Load Capacity (KG)	Max. Load Capacity (LBS)	Max. Air Pressure (KPa)	Max. Air Pressure (PSI)	Tread Depth (mm)	Section Width (mm)	Overall Diameter (mm)
1	55"	215/55R18	SL	OWL	7.0	-	95H	690	1521	350	51	9.4	226	693
2		215/55R18	XL	OWL	7.0	-	99V	775	1709	340	50	9.4	226	693
3		215/60R17	SL	OWL	6.5	-	96H	710	1565	350	51	9.4	221	690
4	60"	235/60R18	SL	OWL	7.0	-	103H	875	1929	350	51	9.4	240	739
5		235/60R18	SL	OWL	7.0	-	103V	875	1929	350	51	9.4	240	739
6	65"	235/65R17	SL	OWL	7.0	-	104T	900	1984	350	51	9.4	240	738
7		245/65R17	SL	OWL	7.0	-	107T	975	2149	350	51	9.8	248	750
8		265/65R17	SL	OWL	8.0	-	112H	1120	2469	350	51	9.8	272	776
9	70"	215/70R16	SL	OWL	6.5	-	100H	800	1764	350	51	9.4	221	708
10		225/70R16	SL	OWL	6.5	-	103T	875	1929	350	51	9.4	228	722
11		235/70R16	SL	OWL	7.0	-	106T	950	2094	350	51	9.4	240	736
12		245/70R16	XL	BSW	7.0	-	111T	1090	2403	340	50	9.8	248	750
13		245/70R16	SL	OWL	7.0	-	107T	975	2149	350	51	9.8	248	750
14		265/70R16	SL	OWL	8.0	-	112T	1120	2469	350	51	9.8	272	778
15		265/70R17	SL	OWL	8.0	-	115T	1215	2679	350	51	9.8	272	804
16		LT265/70R17	-	BSW	8.0	10	121/118R	1450/1320	3195/2910	550	80	11.3	272	804
17		LT285/70R17	-	BSW	8.5	8	121/118S	1450/1320	3195/2910	450	65	11.3	292	832
18	75"	235/75R15	XL	OWL	6.5	-	109T	1030	2271	340	50	9.4	235	733
19		265/75R16	SL	OWL	7.5	-	116T	1250	2756	350	51	9.8	267	804
20		31X10.50R15LT	-	BSW	8.5	6	109R	1030	2270	350	50	11.3	268	775
21		LT215/75R15	-	OWL	6.0	8	106/103R	950/875	2095/1930	450	65	11.3	216	703
22		LT225/75R16	-	BSW	6.0	10	115/112R	1215/1120	2680/2470	550	80	11.3	223	744
23		LT235/75R15	-	OWL	6.5	10	116/113S	1250/1150	2755/2535	550	80	11.3	235	733
24		LT245/75R16	-	BSW	7.0	10	120/116R	1400/1250	3085/2755	550	80	11.3	248	774
25		LT245/75R17	-	BSW	7.0	10	121/118R	1450/1320	3195/2910	550	80	11.3	248	800
26		LT265/75R16	-	BSW	7.5	10	123/120R	1550/1400	3415/3085	550	80	11.3	267	804
27		80"	LT235/80R17	-	BSW	6.5	10	120/117R	1400/1285	3085/2835	550	80	11.3	235
28	85"	LT235/85R16	-	BSW	6.5	10	120/116R	1400/1250	3085/2755	550	80	11.3	235	806