

VAN

TRAVIA VAN

Long Mileage Solution

- High abrasion tread compound to enhance expected mileage markedly.

All-weather Grip Solution

- Three straight mian pattern grooves to enhance outstanding wet grip.



High Load Solution

- Reinforced tyre body and band structure to provide stronger load capacity.

NO.	Series	Size	SL/XL	Sidewall Type	Rim	PR	LI/SS	Max. Load Capacity (KG)	Max. Load Capacity (LBS)	Max. Air Pressure (KPa)	Max. Air Pressure (PSI)	Tread Depth (mm)	Section Width (mm)	Overall Diameter (mm)
1	60"	215/60R16C	-	BSW	6.5	8	103/101T	875/825	1929/1819	375	54	9.7	221	664
2		175/65R14C	-	BSW	5.0	6	90/88T	600/560	1323/1235	375	54	9.7	177	584
3		205/65R16C	-	BSW	6.0	8	107/105T	975/925	2149/2039	475	69	9.7	209	672
4	65"	215/65R16C	-	BSW	6.5	8	109/107R	1030/975	2271/2149	475	69	9.7	221	686
5		225/65R16C	-	BSW	6.5	8	112/110R	1120/1060	2469/2337	475	69	9.7	228	698
6		235/65R16C	-	BSW	7.0	8	115/113R	1215/1150	2679/2535	475	69	9.7	240	712
7		165/70R13C	-	BSW	5.0	6	88/86R	560/530	1235/1168	375	54	9.7	170	562
8		165/70R14C	-	BSW	5.0	6	89/87R	580/545	1279/1201	375	54	9.7	170	588
9		175/70R14C	-	BSW	5.0	6	95/93R	690/650	1521/1433	375	54	9.7	177	602
10	70"	195/70R15C	-	BSW	6.0	8	104/102R	900/850	1984/1874	450	65	9.7	201	655
11		205/70R15C	-	BSW	6.0	8	106/104R	950/900	2094/1984	450	65	9.7	209	669
12		215/70R15C	-	BSW	6.5	8	109/107R	1030/975	2271/2149	450	65	9.7	221	683
13		225/70R15C	-	BSW	6.5	8	112/110R	1120/1060	2469/2337	450	65	9.7	228	697
14		185/75R16C	-	BSW	5.0	8	104/102R	900/850	1984/1874	475	69	9.7	184	684
15	75"	195/75R16C	-	BSW	5.5	8	107/105R	975/925	2149/2039	475	69	9.7	196	698
16		205/75R16C	-	BSW	5.5	8	110/108R	1060/1000	2337/2205	475	69	9.7	203	714
17		215/75R16C	-	BSW	6.0	8	113/111R	1150/1090	2535/2403	475	69	9.7	216	728
18		155R12C	-	BSW	4.5	8	88/86Q	560/530	1235/1168	450	65	9.7	157	550
19		155R13C	-	BSW	4.5	6	85/83Q	515/487	1135/1074	350	50	9.7	157	578
20		165R13C	-	BSW	4.5	6	91/89Q	615/580	1356/1279	350	50	9.7	167	596
21		185R14C	-	BSW	5.5	8	102/100Q	850/800	1874/1764	450	65	9.7	188	650
22	80"	195R14C	-	BSW	5.5	8	106/104Q	950/900	2094/1984	450	65	9.7	198	666
23		195R15C	-	BSW	5.5	8	106/104Q	950/900	2094/1984	450	65	9.7	196	693
24		205R14C	-	BSW	6.0	8	109/107Q	1030/975	2271/2149	450	65	9.7	208	686
25		205R16C	-	WSW	6.0	8	110/108R	1060/1000	2337/2205	450	65	9.7	208	736