

# UHP U11




- Fuel Economy**  
 The special tread compound reduces rolling resistance to provide more efficient fuel consumption.
- Driving Comfort**  
 The varying pitch order and block sipe design better absorb vibrations emitted from the tire for a quieter ride.
- Tread Pattern**  
 The asymmetric tread pattern contains a center rib for strong grip and handling which allows for precision steering and braking. The four wide grooves are inlaid with horizontal notches which enhance water expulsion for great handling in wet conditions.

RIM	SIZE	LI/SS		T.D.	STANDARD RIM	S.W.	O.D.	MAX.LOAD	MAX.PRESSURE	UTQG	SIDEWALL
				mm	inch	mm	mm	KG	kPa		
15	185/45ZR15	75Y		7.5	6J	183	547	387	300	280/AAA	BSW
16	205/50ZR16	87W		8	6 1/2J	214	612	545	300	280/AAA	BSW
16	205/55ZR16	94W	XL	8.2	6 1/2J	214	632	670	340	280/AAA	BSW
16	215/45ZR16	90Y	XL	7.5	7J	213	600	600	340	280/AAA	BSW
16	215/55ZR16	97W	XL	8.2	7J	226	642	730	340	280/AAA	BSW

1inch=25.4mm   1kPa=0.142psi   1KG=2.2 lbs   XL Extra Load   LI Load Index   SS Speed Symbol


## ROADX



**U11** Innovative  
**high performance tire**  
 that combines comfort with low  
 fuel consumption



# UHP U11



RIM	SIZE	LI/SS		T.D.	STANDARD RIM	S.W.	O.D.	MAX.LOAD	MAX.PRESSURE	UTQG	SIDEWALL
				mm	inch	mm	mm	KG	kPa		
17	185/45ZR17	82Y	XL	7.5	6J	183	598	475	340	280/AA/A	BSW
17	195/40ZR17	81Y	XL	7.5	7J	200	588	462	340	280/AA/A	BSW
17	195/45ZR17	85Y	XL	7.5	6 1/2J	195	608	515	340	280/AA/A	BSW
17	205/40ZR17	84W	XL	8	7 1/2J	212	596	500	340	280/AA/A	BSW
17	205/45ZR17	88W	XL	8	7J	206	616	560	340	280/AA/A	BSW
17	205/50ZR17	93W	XL	8	6 1/2J	214	638	650	340	280/AA/A	BSW
17	205/55ZR17	95Y	XL	7.5	6 1/2J	214	658	690	340	280/AA/A	BSW
17	215/40ZR17	87Y	XL	7.5	7 1/2J	218	604	545	340	280/AA/A	BSW
17	215/45ZR17	91W	XL	8	7J	213	626	615	340	280/AA/A	BSW
17	215/50ZR17	95W	XL	--	7J	226	648	690	340	280/AA/A	BSW
17	215/55ZR17	94W	--	8	7J	226	668	670	300	280/AA/A	BSW
17	225/45ZR17	94W	XL	8	7 1/2J	225	634	670	340	280/AA/A	BSW
17	225/50ZR17	98W	XL	8.2	7J	233	658	750	340	280/AA/A	BSW
17	225/55ZR17	101W	XL	8.2	7J	233	680	825	340	280/AA/A	BSW
17	235/45ZR17	97W	XL	8.2	8J	236	644	730	340	280/AA/A	BSW
17	235/50ZR17	100Y	XL	7.5	7 1/2J	245	668	800	340	280/AA/A	BSW
17	245/40ZR17	95W	XL	8	8 1/2J	248	628	690	340	280/AA/A	BSW
17	245/45ZR17	99Y	XL	7.5	8J	243	652	775	340	280/AA/A	BSW
18	215/35ZR18	84Y	XL	7.5	7 1/2J	218	607	500	340	280/AA/A	BSW
18	215/40ZR18	89Y	XL	7.5	7 1/2J	218	629	580	340	280/AA/A	BSW
18	215/45ZR18	93Y	XL	7.5	7J	213	651	650	340	280/AA/A	BSW
18	225/35ZR18	87Y	XL	7.5	8J	230	615	545	340	280/AA/A	BSW
18	225/40ZR18	92W	XL	8	8J	230	637	630	340	280/AA/A	BSW
18	225/45ZR18	95W	XL	8	7 1/2J	225	659	690	340	280/AA/A	BSW
18	235/35ZR18	90Y	XL	7.5	8 1/2J	241	621	600	340	280/AA/A	BSW
18	235/40ZR18	95W	XL	8	8 1/2J	241	645	690	340	280/AA/A	BSW
18	235/45ZR18	98Y	XL	7.5	8J	236	669	750	340	280/AA/A	BSW
18	245/35ZR18	92Y	XL	7.5	8 1/2J	248	629	630	340	280/AA/A	BSW
18	245/40ZR18	97Y	XL	8	8 1/2J	248	653	730	340	280/AA/A	BSW
18	255/35ZR18	94Y	XL	8	9J	260	635	670	340	280/AA/A	BSW
18	255/40ZR18	99Y	XL	7.5	9J	260	661	775	340	280/AA/A	BSW
18	255/45ZR18	103Y	XL	7.5	8 1/2J	255	687	875	340	280/AA/A	BSW
18	265/35ZR18	97Y	XL	7.5	9 1/2J	271	643	730	340	280/AA/A	BSW
18	275/40ZR18	103Y	XL	7.5	9 1/2J	278	677	875	340	280/AA/A	BSW

1inch=25.4mm | 1kPa=0.142psi | 1KG=2.2 lbs | XL Extra Load | LI Load Index | SS Speed Symbol

RIM	SIZE	LI/SS		T.D.	STANDARD RIM	S.W.	O.D.	MAX.LOAD	MAX.PRESSURE	UTQG	SIDEWALL
				mm	inch	mm	mm	KG	kPa		
19	215/35ZR19	85Y	XL	7.5	7 1/2J	218	633	515	340	280/AA/A	BSW
19	225/35ZR19	88Y	XL	7.5	8J	230	641	560	340	280/AA/A	BSW
19	225/40ZR19	93Y	XL	7.5	8J	230	663	650	340	280/AA/A	BSW
19	235/35ZR19	91Y	XL	8	8 1/2J	241	647	615	340	280/AA/A	BSW
19	235/40ZR19	96Y	XL	7.5	8 1/2J	241	671	710	340	280/AA/A	BSW
19	235/45ZR19	99Y	XL	7.5	8J	236	695	775	340	280/AA/A	BSW
19	245/35ZR19	93Y	XL	8	8 1/2J	248	655	650	340	280/AA/A	BSW
19	245/40ZR19	98Y	XL	8	8 1/2J	248	679	750	340	280/AA/A	BSW
19	245/45ZR19	102Y	XL	7.5	8J	243	703	850	340	280/AA/A	BSW
19	255/30ZR19	91Y	XL	7.5	9J	260	637	615	340	280/AA/A	BSW
19	255/35ZR19	96Y	XL	8	9J	260	661	710	340	280/AA/A	BSW
19	255/45ZR19	104W	XL	8	8 1/2J	226	693	900	340	280/AA/A	BSW
19	255/50ZR19	107Y	XL	8	8J	265	739	975	340	280/AA/A	BSW
19	265/30ZR19	93Y	XL	8	9 1/2J	271	643	650	340	280/AA/A	BSW
19	265/35ZR19	98Y	XL	7.5	9 1/2J	271	669	750	340	280/AA/A	BSW
19	275/30ZR19	96Y	XL	8	9 1/2J	278	649	710	340	280/AA/A	BSW
19	275/35ZR19	100Y	XL	8	9 1/2J	278	675	800	340	280/AA/A	BSW
19	275/40ZR19	105Y	XL	7.5	9 1/2J	278	703	925	340	280/AA/A	BSW
19	275/45ZR19	108Y	XL	7.5	9J	273	731	1000	340	280/AA/A	BSW
19	285/45ZR19	111Y	XL	8	9 1/2J	285	739	1090	340	280/AA/A	BSW
20	225/30ZR20	85Y	XL	7.5	8J	230	644	515	340	280/AA/A	BSW
20	245/35ZR20	95Y	XL	7.5	8 1/2J	248	680	690	340	280/AA/A	BSW
20	245/40ZR20	99Y	XL	7.5	8 1/2J	248	704	775	340	280/AA/A	BSW
20	255/35ZR20	97Y	XL	7.5	9J	260	686	730	340	280/AA/A	BSW
20	255/40ZR20	101Y	XL	7.5	9J	260	712	825	340	280/AA/A	BSW
20	265/50ZR20	111Y	XL	7.5	8 1/2J	277	774	1090	340	280/AA/A	BSW
20	275/35ZR20	102Y	XL	7.5	9 1/2J	278	700	850	340	280/AA/A	BSW
20	275/40ZR20	106Y	XL	8	9 1/2J	278	728	950	340	280/AA/A	BSW
20	275/45ZR20	110Y	XL	8	9J	273	756	1060	340	280/AA/A	BSW
20	295/35ZR20	105Y	XL	7.5	10 1/2J	301	714	925	340	280/AA/A	BSW
20	315/35ZR20	110Y	XL	8	11J	320	728	1060	340	280/AA/A	BSW
21	285/35ZR21	105Y	XL	8	10J	290	733	925	340	280/AA/A	BSW
21	295/35ZR21	107Y	XL	8	10 1/2J	301	739	975	340	280/AA/A	BSW
21	325/30ZR21	108Y	XL	8	11 1/2J	331	729	1000	340	280/AA/A	BSW
22	265/40ZR22	106Y	XL	7.5	9 1/2J	271	771	950	340	280/AA/A	BSW

1inch=25.4mm | 1kPa=0.142psi | 1KG=2.2 lbs | XL Extra Load | LI Load Index | SS Speed Symbol